



PRI Evaluation Report

PRI ER 2274E03-LA

Issue Date: October 7, 2024

Last Revision: Original Issue

Visit: pri-group.com for current status.

Report Holder: **W.R. Meadows, Inc.**
300 Industrial Drive
Hampshire, IL 60140
wrmeadows.com

SCOPE

Subject: Dampproofing and Waterproofing

Product:
PRECON

CSI MasterFormat®:
DIVISION: 07 00 00 – THERMAL AND MOISTURE PROTECTION
Sub-level 2: 07 13 00 – Sheet Waterproofing

Code Reference:
• 2020 City of Los Angeles Building Code

Properties Evaluated:

- Physical Properties (LADBS AC-L021)

Evidence Submitted:

- Recognized test report(s) indicating compliance with LADBS AC-L021
- Quality Documentation
- Manufacturer's Drawings and Installation Instructions

Manufacturing Locations:

<u>Factory ID</u>	<u>Location</u>
Hampshire, IL	300 Industrial Drive Hampshire, IL 60140

PRODUCT DESCRIPTIONS and APPLICATIONS

<u>Product with Description:</u>	<u>Factory IDs:</u>	<u>Packaging:</u>
PRECON Product is a blindside waterproofing composite sheet membrane comprised of a non-woven fabric, elastomeric membrane, and PLAMSTIC CORE.	Hampshire, IL	Length: 50 ft Width: 4 ft

Uses:

PRECON is approved for use when required by Section 1805 Dampproofing and Waterproofing. PRECON is limited to a maximum hydrostatic pressure resistance of 287 psi.

The membrane shall not be exposed to sunlight when installed in accordance with the published manufacturer's installation details. The membrane shall not be used with pneumatically applied concrete (gunite or shotcrete).

INSTALLATION

Apply at temperatures 40°F and above.

All surfaces to receive the membrane shall be free of large voids, sharp projections, and standing water. Inspect and treat the surfaces prior to application in accordance with the manufacturer's published installation details.

Install PRECON in accordance with the manufacturer's published installation details.

Protection of the waterproofing membrane shall be provided

in accordance with the manufacturer's published installation details.

Concrete shall be poured within 60 days of membrane installation.



CONDITIONS OF USE & IDENTIFICATION

The products described in this report comply with, or are suitable alternatives to, the codes listed in this report, subject to the following conditions:

- The products as well as the installation methods must be in compliance with the applicable code, this report, and the installation instruction provided by the manufacturer. If the manufacturer's installation instructions differ from what is listed in this report, this report governs.
- This report does not supersede the local jurisdiction regulations and the final approval of the building products, materials, or systems in this report is the responsibility of the authorities having jurisdiction.
- This report is only valid if the product(s) and/or the referenced documentation/codes related to the products do not change. If there is a change in product(s) and/or the referenced documentation/codes related to the products, PRI Construction Materials Technologies, LLC must be informed and further action may be necessary to revalidate this report.
- This report, in its entirety, must be available at job sites upon request by the user or for inspection by the Building Official. A copy of this report in full shall be provided by the manufacturer or its distributors.
- The products are identified by marks bearing the report holder's name, the manufacture location, the product name, and the Seal of PRI Validation Program for Building Materials. The Seal shall indicate, at a minimum, the following:
 - a. LADBS AC-L021
- The products are manufactured at the locations listed in this report and are manufactured under a quality control program with inspections and/or surveillance by PRI Construction Materials Technologies, LLC.
- This report is a supplement to product certification. The products listed herein must be certified separately under the PRI Validation Program for Building Products. This report alone is not a product certification and requires separate product certification under the PRI Validation Program for Building Products to be valid.
- The current status of this report as well as a directory of certified products, including supplemental PRI Evaluation Reports, can be found at pri-group.com.

© 2024 PRI Construction Materials Technologies, LLC

This PRI Evaluation Report is for the exclusive use by the Client with which a signed agreement was made with PRI Construction Materials Technologies, LLC. PRI Construction Materials Technologies, LLC is only responsible and/or liable for the terms and conditions outlined in that signed agreement. Only the Client has authority to distribute or authorize distribution of the report in its entirety and they shall not do so in a misleading manner. Any loss, expense, or damage caused by the use of this report to any party, other than the Client in accordance with the agreement, is not the responsibility or fault of PRI Construction Materials Technologies, LLC. PRI Construction Materials Technologies, LLC has no financial interest, nor does it have intent to acquire financial interest, in the manufacture or the distribution of the product(s) listed in this report. PRI Construction Materials Technologies, LLC is not under the ownership, operation, or control of the manufacturer or the distributor of the product(s) listed in this report. PRI Construction Materials Technologies, LLC does not guarantee any representations or warranties on any product(s) or subjects contained in this report. This PRI Evaluation Report is an evaluation of building code and is in no way an endorsement or a recommendation for use for the product(s) listed within. All data utilized in support of this report comes from accredited laboratories that show compliance with ISO/IEC Standard 17025 by the International Accreditation Service (IAS) or by any other accreditation body that is a signatory to the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Arrangement (MRA). The accuracy of any data that comes from an accredited laboratory that is not PRI Construction Materials Technologies, LLC is the responsibility of the publishing laboratory alone; PRI Construction Materials Technologies, LLC does not accept any responsibility for the accuracy of this data.